



LED Sensor Solar Folding Wall Light Range

Code	Description
ESOL2.5W-WH / BL	2.5W 230Lm 4000k ABS IP44 White or Black Radar Sensor Solar
ESOL3.5W-WH / BL	3.5W 340Lm 4000k ABS IP44 White or Black Radar Sensor Solar
ESOL7.5W-WH / BL	7.5W 700Lm 4000k ABS IP44 White or Black Radar Sensor Solar

FEATURES


- Power: 2.5w / 3.5w / 7.5W
- Max Lumen: 230Lm / 340Lm / 700Lm
- Min Lumen: 207Lm / 306Lm / 620Lm
- Colour Temp: 4000k
- Radar Sensor 0-6M, 120°
- Charging time: 4-6 hrs
- Operating time: 6-8 hrs
- Working Voltage: 6v
- Beam Angle: 100°
- Lightweight, foldable
- IP44 - for outdoor use
- Material: ABS
- 2.5W - Battery: 1x 3.7v 1500mAh Li-ion
- 3.5W - Battery: 1x 3.7v 1800mAh Li-ion
- 7.5W - Battery: 1x 3.7v 4800mAh Li-ion
- Charging Temp: 0°C~45°C
- Operating Temp: -10°C~55°C








ESOL2.5W-BL



ESOL2.5W-WH



Wattage	Dimensions
2.5W	L119 x W93mm
3.5W	L167 x W93mm
7.5W	L219 x W93mm



Solas Geal Distribution Ltd, Unit 7 & 8 Ashbourne Business Centre, Ballybin Road, Ashbourne, Co. Meath, A84 YP58, Ireland.
 SGD Solas Geal UK Ltd, Unit 32 Junction One Business Park, Valley Road, Birkenhead, Wirral, Merseyside, UK, CH41 7ED.

Tel: +353 1 8357447. UK Ph: 0330 551 7000. Fax: 00353 1 8357448. Email: info@sgd.ie. Website: www.sgd.ie