



LED MULTI WATT CCT IP66 CORROSION PROOF RANGE

Code	Description	Multi Watt	Size
SCP6FTMW-CCT	LED Multi Watt CCT 6ft IP66 Corrosion Proof	80w / 70w / 60w / 50w	6ft
SCP6FTMW-CCT-EM	LED Multi Watt CCT 6ft IP66 Emergency Corrosion Proof	80w / 70w / 60w / 50w	6ft
SCPMW-CCT	LED Multi Watt CCT 5ft IP66 Corrosion Proof	60w / 52w / 43w / 34w	5ft
SCPMW-CCT-EM	LED Multi Watt CCT 5ft Emergency IP66 Corrosion Proof	60w / 52w / 43w / 34w	5ft
SCPMW-CCT-SENEM	LED Multi Watt CCT 5ft Emergency Sensor IP66 Corrosion Proof	60w / 52w / 43w / 34w	5ft
SCPMW-CCT-SEN	LED Multi Watt CCT 5ft Sensor IP66 Corrosion Proof	60w / 52w / 43w / 34w	5ft
SCP4FTMW-CCT	LED Multi Watt CCT 4ft IP66 Corrosion Proof	40w / 34w / 28w / 22w	4ft
SCP4FTMW-CCT-EM	LED Multi Watt CCT 4ft IP66 Emergency Corrosion Proof	40w / 34w / 28w / 22w	4ft
SCP2FTMW-CCT	LED Multi Watt CCT 2ft IP66 Corrosion Proof	20w / 18w / 15w / 11w	2ft

5 years Quality Assurance

IP66

160 Lm/W

BOX QUANTITY
 6FT = 6
 5FT = 6
 4FT = 6
 2FT = 8

Features

- Multi Watt
- 160LM/W
- CCT: 4000k, 5000k, 6000k
- SMD 2835
- SS Clips
- RA>80
- IP66
- Beam Angle: 110°
- Battery 3 yr Warranty
- Battery Type: LiFeP04 6.4V 2000mAh
- 3hr maintained emergency back up
- Transmitting power: <0.5mW
- Power Consumption: ≤0.5mW(standby) <1W(operation)
- Detection zone: Max(D x H):12m x 6m
- Detection Angle:150° (Wall Installation) 360° (Ceiling Installation)
- Detection sensitivity: 10%/ 25%/50%/75%/100%
- Operating Temp: -20°C~50°C
- Operating Voltage: 220~240Vac, 50Hz



Download Specification



Solas Geal Distribution Ltd, Unit 7 & 8 Ashbourne Business Centre, Ballybin Road, Ashbourne, Co. Meath, A84 YP58, Ireland.
 SGD Solas Geal UK Ltd, Unit 32 Junction One Business Park, Valley Road, Birkenhead, Wirral, Merseyside, UK, CH41 7ED.

Tel: +353 1 8357447. UK Ph: 0330 551 7000. Fax: 00353 1 8357448. Email: info@sgd.ie. Website: www.sgd.ie